



50000 P - RAP. 7:1

Web: <https://www.witsrl.com/>

Email: info@witsrl.com

SKU: 50200

Categories: [Industry pumps](#), [Pneumatic piston airless pumps](#), [Outdated pumps](#)

DESCRIZIONE DEL PRODOTTO

50000 P has a flow rate of 50 lt/min and with different air engines can be supplied with a 3:1 or 7:1 compression ratio.

Upon request, this model includes the fitting of a special large-capacity stainless steel filter.

THE AIRLESS SYSTEM

The airless method allows a considerable reduction of overspray with three important advantages: reduced paint consumption, considerable working speed, and reduced environmental pollution.

CONSTRUCTION SPECIFICATIONS

The air motors used are TAIVER's patented rapid volumetric reversing type, do not require lubrication and are not subject to freezing. All parts in contact with the product to be pumped are made of stainless steel so they are also suitable for food or acidic products. The valve seats are made of nickel alloyed tungsten carbide. 25000 P and 50000 P are set up to be able to fit different air engines according to the compression ratio needed

THE REVOLUTIONARY TRANSFER PUMPS!

The 25000 P and 50000 P pneumatic transfer pumps are designed with Taiver's more than 30 years' experience in the industry. Ideal for pumping and decanting food products, self-levelling agents, inks, oils, even dense oils, in cataphoresis baths in paint distribution plants and in any other case with viscosity products up to 100,000 centipoise.

APPLICATIONS' FIELD

- Food industry
- Chemical Industry