



## HYDRA TURBO TWIN

Web: <https://www.witsrl.com/>

Email: [info@witsrl.com](mailto:info@witsrl.com)

---

**SKU:** 21460

**Categories:** [Injection pumps](#), [Bi-component injection series](#), [Building Pumps](#), [Hydraulic piston airless pumps](#), [Two-component pumps](#), [Hydraulic piston airless pumps](#)

### Dati Tecnici:

**Power:** 2.6 kW or 5.5 kW

**Flow rate with MAX nozzle:** 6.5 L/m per pumping unit

**MAX pressure:** 220 bar

**Pipe elevation MAX:** 100 m

**Suggested MAX viscosity:** 50,000 / 65,000 mPas

**Stroke volume:** 73 cc

**Voltage:** 230V/50Hz or 400V/50Hz

**Amperage:** 13A-16A

**Mixing ratio:** continuously variable (0:1 to 1:1)

**MAX flow rate:** 9 L/m per pump

**Hose length MAX:** 100 m

**Weight:** approx. 100 kg

**Gasket pack:** mobile

|

## DESCRIZIONE DEL PRODOTTO

Electro-hydraulic pump with 2 independent pumps, for the simultaneous application of products with different characteristics such as viscosity or colour.

Able therefore, in the field of industrial painting, to independently feed 2 OPERATORS with 2 AIRLESS PISTOLS simultaneously.

Effective particularly in the field of BI-COMPONENT RESIN injections with fixed or variable ratio, from 0 to over 200 bar.

The 2 pumps are continuously adjustable, independently of each other, to obtain any mixing ratio of the two products A and B, from 0:1 to 1:1.