



HYDRA TURBO TWIN

Web: <https://www.witsrl.com/>

Email: info@witsrl.com

SKU: 21460

Categories: [Building Pumps](#), [Hydraulic piston airless pumps](#), [Two-component pumps](#), [Hydraulic piston airless pumps](#), [Injection pumps](#), [Bi-component injection series](#)

Dati Tecnici:

Power: 2.6 kW or 5.5 kW

Flow rate with MAX nozzle: 6.5 l/m per pumping unit

MAX pressure: 220 bar

Pipe elevation MAX: 100 m

Suggested MAX viscosity: 50,000 / 65,000 mPas

Stroke volume: 73 cc

Voltage: 230V/50Hz or 400V/50Hz

Amperage: 13A-16A

Mixing ratio: continuously variable (0:1 to 1:1)

MAX flow rate: 9 l/m per pump

Hose length MAX: 100 m

Weight: approx. 100 kg

Gasket pack: mobile

|

DESCRIZIONE DEL PRODOTTO

Electro-hydraulic pump with 2 independent pumps, for the simultaneous application of products with different characteristics such as viscosity or colour.

Able therefore, in the field of industrial painting, to independently feed 2 OPERATORS with 2 AIRLESS PISTOLS simultaneously.

Effective particularly in the field of BI-COMPONENT RESIN injections with fixed or variable ratio, from 0 to over 200 bar.

The 2 pumps are continuously adjustable, independently of each other, to obtain any mixing ratio of the two products A and B, from 0:1 to 1:1.