



MATIK HVLP

Web: <https://www.witsrl.com/>

Email: info@witsrl.com

SKU: 3270XX

Categories: [Spray guns](#), [Automatic air guns](#)

Dati Tecnici:

MAX working pressure: 8 bar

Contact parts: 250 L/min.

Needle-Molle: Stainless steel

Nozzle: Stainless steel AISI 303

Body: Extruded anodized aluminum

Fitting: M 1/4

Cap: Chemically nickel-plated brass

Seal gaskets: self-lubricating PTFE (Teflon)

Nozzle diameter: 0.8 – 1.0 – 1.2 – 1.3 – 1.4 – 1.7

|

DESCRIZIONE DEL PRODOTTO

Innovativo aerografo automatico per la verniciatura industriale. With a new design, MATIK combines the high product atomization features with the needs typical of the automatic painting sector such as component durability and extreme maintenance ease.

In fact, MATIK combines highly pulverising caps, from the bodywork sector, with perfect needle interference on the nozzle which, with CNC machine processed body and components, guarantee efficiency, reliability and durability.

Available in the MATIK GEO versions, thus ecological with double atomization nozzle recommended for Car Refinish; MATIK HVLP, recommended for industrial and wood applications; MATIK HTE, the high transfer efficiency version with high atomization, ideal for any type of application.

Air and control inlets: with rotary quick couplings (M 1/4" double product inlet)

- **Body:** extruded anodised aluminium
- **Cap:** nickel-plated brass
- **Nozzle:** AISI 303 stainless steel
- **Needle-spring:** stainless steel
- **Spring return needle** closing
- **Seal gaskets:** self-lubricating PTFE (Teflon)
- **Fan and needle opening adjustments:** micrometric and independent
- **Weight:** 835 g
- **Operating pressure:** 2.0 bar
- **Air consumption:** 250 l/min.
- **Nozzle Ø:** 0.8 – 1.0 – 1.2 – 1.3 – 1.4 – 1.7