



W 5000 P (30:1)

Web: <https://www.witsrl.com/>

Email: info@witsrl.com

SKU: 27002

Categories: [Industry pumps](#), [Pneumatic piston airless pumps](#), [Pumps for carpentry](#)

Dati Tecnici:

Compression ratio: 32:1

MAX pressure: 250 bar

Suggested MAX viscosity: 600 Centipoise

Stroke volume: 27 cc

MAX inlet air pressure: 8 bar

MAX flow rate: 5 l/m

MAX nozzle size: 0.027

Weight: 19 kg

Seal pack: fixed

|

DESCRIZIONE DEL PRODOTTO

PNEUMATIC AIRLESS PUMP W 5000 P STAINLESS STEEL, 30: 1, COMPLETE WITH CART AND PRESSURE REGULATOR

It is a pneumatic piston pump driven by an instant volumetric reversal air motor which allows to use the equipments with a small air lubrication and has no freezing trouble and a very low pressure drop during the reversal. Extremely functional, they are ideal for spraying both light products such as paints or enamels and more viscous paints such as primers or water-based varnishes. Used in airless or AirMix mode, they are available on an elegant trolley with wheels or on a fixed trolley (in the version with direct suction from the drum).

- * Easy maintenance
- * Universal pump
- * Gasket type: Fixed

APPLICATIONS

Alcohol, Anti roar, Adhesives, Detergents, Release agents, Epoxy, Greases, Vegetable greases, Water-based paints, Inks, Lubricants, Mastics, Oils, Sealants, Solvents, Spot, Sealers, Paints, Oil-based paints, Acrylic paints

APPLICATION'S FIELDS

Craftsmen • Carpentry • Wood industry • Railways industry • Automotive industry • Construction industry • Mechanical Engineering • Shipyard